

QT-PTC100W - 100W PTC HEATER



- » Pressure Clamp Connectors
- » Dynamic Heating Up
- » Wide Voltage Range
- » Energy Saving
- » Clip Fixing
- » Quick Installation



Industrial Grade



2 Years Warranty



DIN Rail Mount

TECHNICAL PARAMETER

| | |
|-----------------------|---|
| Heating Capacity | 100W |
| Supply Voltage | 120-240V AC/DC (min. 110V, max. 265V) |
| Inrush Current max. | 4.5A |
| Heating Element | PTC Resistor, Self-regulating & Temp. Limiting |
| Heater Body | Extruded Aluminium Profile, Anodized |
| Connection | 3 Pressure clamps for stranded wire 0.5-1.5mm ² (with wire end ferrule) and rigid wire 0.5- 2.5mm ² |
| Connection Casing | Plastic according to UL94 V-0, black |
| Mounting | Vertical Airflow (Air outlet up, connection on bottom) |
| Fitting Position | Variable |
| Operating Temperature | -45 To +70°C (-49 to +158°F) |
| Operating Humidity | max. 90% RH (non-condensing) |
| Length | 140 mm |
| Weight | 500 gm |
| Protection Type | IP20 / I (Earthed) |
| Certification | CE, RoHS Compliance |

DIMENSIONS

