

QT-8UGPETH - 8 PORT UNMANAGED GIGABIT PoE ETHERNET SWITCH



- » 5x1000M Ethernet Port
- » Supply : 48V DC
- » Anti-static: 8KV-15KV
- » MTBF: 100000 Hours
- » Ingress Protection : IP40
- » Operating Temp.: -30°C ~ +75°C



Industrial Grade



Years Warranty



Redundant Power



24x7 Hours Stable Operation



PoE Version



Gigabit Version



DIN Rail Mount



High & Low Temperature Resistance

This QT-8UGPETH is 8x10/100/1000 Base-T Industrial PoE Ethernet Switch. Through the fan-less heat dissipation circuit design, wide range of working environment temperature, high protection level and other technologies, it provides excellent industrial quality with high/low temperature resistance and lightning protection, and enhances the reliability and safety of industrial networks. The device can be widely applied to various broadband data transmission fields such as intelligent transportation, telecommunications, security, financial securities, customs, shipping, power, water conservancy and oil fields.

TECHNICAL DETAILS

Copper Port	8 x 10/100/1000Base-T
Power Interface	Phoenix Terminal, Dual Power Supply (P1,P2)
Switching	16Gbps
Packets Forwarding Rate	11.9Mbps
MAC Address Table	4K
Port Buffer	2M
Surge Protection of Power	IEC 61000-4-5 Level 3 (4KV/2KV) (8/20us)
Surge protection of Port	IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us)
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Free Fall	0.5m
Power Input	48-58V DC
PoE budget	240W



QT-8UGPETH - 8 PORT UNMANAGED GIGABIT PoE ETHERNET SWITCH

TECHNICAL DETAILS

PoE Port	1-8
PoE Protocol	IEEE802.3 af/at standard
PIN Sequence	1,2+/3,6-
Housing	IP40-rated Aluminum Alloy, Fan-less design
Working temperature	-20 °C ~70°C
Storage temperature	-30 °C ~70 °C
Operating humidity	10%~90% @30°C, no condensation
Product Size	143 x 104 x 46 mm
Weight	Net : 400 gm Gross : 500 gm
Installation method	DIN-rail Mounting (35mm)
MTBF	1,00,000 hours

DIMENSIONS

