

QT-11MCSFP - 1+1 SFP TYPE MEDIA CONVERTER



- » DIN Rail Mount
- » Supply : 24V DC
- » Anti-static: 8KV-15KV
- » MTBF: 100000 Hours
- » Ingress Protection : IP40
- » Operating Temp.: -30°C ~ +75°C



Years Warranty



Industrial Grade



Wide Voltage Range



24x7 Hours Stable Operation



Redundant Power



DIN Rail Mount



Gigabit Version



High & Low Temperature Resistance

This device is a Gigabit Industrial Ethernet Media Converter. Through fan less cooling circuit design, wide range of working environment temperature, high protection level and other technologies, it provides excellent industrial grade products such as high / low temperature resistance and lightning protection, and enhances the reliability and security of industrial network. It can meet the deployment requirements of rail transit, safe city, intelligent transportation, outdoor monitoring and other harsh environments.

TECHNICAL DETAILS

Copper Port	1 x 1000 Base-X, 1 x 10/100/1000 Base-T
Power Interface	Phoenix Terminal, Dual Power Supply (P1,P2)
DIP Switch	Reserved
Twisted-Pair	0-100m (CAT5e,CAT6)
Fiber optic Interface	SFP Slot
Network Topology Support	Star Topology, Bus Topology, Tree Topology
MAC Address Table	8K
Packet Buffer	1M
Surge Protection of Power	IEC 61000-4-5 Level 3 (4KV/2KV) (8/20us)
Surge protection of Port	IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us)
ESD	IEC 61000-4-2 Level 4 (8K/15K)



QT-11MCSFP - 1+1 SFP TYPE MEDIA CONVERTER

TECHNICAL DETAILS

Power Input	12-58V DC, Dual Redundant
Power Consumption	<5W
Housing	IP40-rated Aluminum Alloy, Fan-less design
Working temperature	-20 °C ~70°C
Storage temperature	-30 °C ~70 °C
Operating humidity	10%~90% @30°C, no condensation
Product Size	118 x 91 x 31 mm
Weight	Net : 400 gm Gross : 500 gm
Installation method	DIN-rail Mounting (35mm)
MTBF	1,00,000 hours

DIMENSIONS

